

Water-Spray Systems

Permanently piped systems of open or automatic water-spray type nozzles are intended for protection of flammable liquid hazards, conveyor openings, horizontal dryers and such.

The automatic control equipment for open nozzle water-spray systems is the same as that used for FM Approved special sprinkler systems. The automatic opening valves are supervised as specified for deluge or preaction systems.

The effectiveness of water-spray protection depends on many factors such as nozzle spacing, elevation, direction or angle of discharge, water pressure, wind velocity and the flashpoint, viscosity and temperature of the flammable liquid to be protected.

Detailed information on proposed installations for FM Global insured locations should be forwarded to the appropriate FM Global district office for review and acceptance. The information should give complete data in regard to the hazard, curbs or overflow drains, type, size, location and angle of nozzles, piping layout, strainers, flushing valves, water pressure available at full flow and control equipment.

Water-spray nozzles are intended to protect a hazard which cannot adequately be protected by conventional sprinkler systems. Each system is designed and calculated for the hazard, and each nozzle is chosen for its specific discharge characteristics (capacity, spray range, spray angle etc.). Applications include protection of spherical tanks, oil-filled electrical equipment, open flammable liquid storage and processing equipment, oil-cooled transformers, conveyor openings, and horizontal continuous dryers.

Open Water- Spray Nozzles

Viking Window Sprinkler

Viking Window Sprinkler. 1/4, 5/16, 3/8, 7/16 in. (6, 8, 10, 11 mm).

Company Name:	The Viking Corp
Company Address:	210 N Industrial Park Dr, Hastings, Michigan 49058, USA
Company Website:	http://www.vikinggroupinc.com
Listing Country:	United States of America
Certification Type:	FM Approved

**VOKR.EX1061
Sprinklers, Outside**[Page Bottom](#)

Sprinklers, Outside[See General Information for Sprinklers, Outside](#)**VIKING CORP**

EX1061

210 N INDUSTRIAL PARK RD
HASTINGS, MI 49058 USA

Viking, Issue C1, VK790, VK791, VK792, VK793, VK794, VK795, VK796 , window type sprinklers. Orifice sizes 1/4, 5/16, 3/8, 7/16, 1/2, 5/8, and 3/4 in.

[Last Updated](#) on 2006-11-29[Questions?](#)[Print this page](#)[Terms of Use](#)[Page Top](#)

© 2012 UL LLC

When the UL Leaf Mark is on the product, or when the word "Environment" is included in the UL Mark, please search the [UL Environment database](#) for additional information regarding this product's certification.

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2012 UL LLC".