

**HMRZ.EX15003  
Gate Valves**[Page Bottom](#)**Gate Valves**[See General Information for Gate Valves](#)**VIKING CORP**

EX15003

210 INDUSTRIAL PARK DR  
HASTINGS, MI 49058-9706 USA

Pattern	Model	Size, in.	End Configuration	Rated Pressure, psig
NRS	NF300F	2.5	Flanged, Grooved, Flanged by Grooved	300
NRS	NF300F	3	Flanged, Grooved, Flanged by Grooved, Mechanical Joint, Flanged by Mechanical Joint	300
NRS	NF300F	4, 6, 8, 10, 12	Flanged, Grooved, Flanged/Grooved, Mechanical Joint, Flange/Mechanical Joint	300
NRS	NF300F	5	Flanged	300
OS&Y	OF300F	2-1/2, 3, 4, 5, 6, 8, 10, 12	Flanged, Grooved, Flanged by Grooved	300
NRS	NF300F	4, 5, 6, 8, 10, 12	Grooved by Grooved	300
NRS	NF200F, NF250F	2.5, 3, 4, 6, 8, 10, 12, 5	Flanged, Grooved, Flanged by Grooved, Mechanical Joint, Flanged by Mechanical Joint, Mechanical Joint, Flange/Mechanical Joint, Grooved by Grooved	200, 250
OS&Y	OF200F, OF250F	2-1/2, 3, 4, 5, 6, 8, 10, 12	Flanged, Grooved, Flanged by Grooved	200, 250
NRS	PIF2	2.5, 3, 4, 5, 6, 8, 10, 12	F by F (ANSI Flange)	300
NRS	PIF	4, 5, 6, 8, 10, 12	F by F (ANSI Flange)	300
NRS	PIG	4, 6, 8, 10, 12	G by G	300
NRS	PIG2	2.5, 3, 4, 5, 6, 8, 10, 12	G by G	300
OS&Y	OSG	2, 2.5, 3, 4, 5, 6, 8, 10, 12	G by G	300
OS&Y	OSF	2, 2.5, 3, 4, 5, 6, 8, 10, 12	F by F	300

[Last Updated](#) on 2015-05-11[Questions?](#)[Print this page](#)[Terms of Use](#)[Page Top](#)

© 2015 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2015 UL LLC".

## Outside Screw and Yoke Gate Valves

Outside screw and yoke gate valves are recommended for service indoors and in pits outdoors. They are not recommended for throttling service. The stem indicates at a glance whether or not the valve is open. Smaller sizes, 3/4 through 2 in. NPS inclusive, are of bronze. Large sizes, 2 1/2 through 14 in. NPS inclusive, are of iron, bronze mounted. One manufacturer makes valves of bronze up through the 3 in. size. Unless otherwise noted in the listing, these valves have 175 psi (1205 kPa) rated working pressure.

### FIREKING Fig. No. OF300F, OG300F, OFG300F

Resilient Seated Gate Valve. Rated Working Pressure 300 psi (2070 kPa). Available with the end connections listed below:

<b>Model No.</b>	<b>Size in. (mm)</b>	<b>End Connections</b>
FIREKING Fig. No. OF300F	2 1/2, 3, 4, 5, 6, 8, 10, 12 (65, 80, 100, 125, 150, 200, 250 and 300)	Flange × Flange (ANSI, ISO, JIS)
FIREKING Fig. No. OG300F	2 1/2, 3, 4, 5, 6, 8, 10, 12 (65, 80, 100, 125, 150, 200, 250 and 300)	Groove × Groove (ANSI, ISO, JIS)
FIREKING Fig. No. OFG300F	2 1/2, 3, 4, 5, 6, 8, 10, 12 (65, 80, 100, 125, 150, 200, 250 and 300)	Flange × Groove (ANSI, ISO, JIS)

<b>Company Name:</b>	The Viking Corp
<b>Company Address:</b>	210 N Industrial Park Dr, Hastings, Michigan 49058, USA

<b>Company Website:</b>	<a href="http://www.vikinggroupinc.com">http://www.vikinggroupinc.com</a>
<b>Listing Country:</b>	United States of America
<b>Certification Type:</b>	FM Approved

## Inside Screw Gate Valves

Inside screw gate valves are used underground with indicator posts attached or as roadway box valves (curb box installation). FM Approved valves are available with a variety of end connections as indicated in the listings.

Valves having Ring-Tite, Fluid-Tite or Tyton-Joint connections should be anchored in place during installation. Unless otherwise noted in the listing, these valves have 175 psi (1205 kPa) rated working pressure.

### FIREKING Fig. No. NF300F, NG300F, NFG300F

Resilient Seated Gate Valve. Available with an indicator post flange. Rated Working Pressure 300 psi (2070 kPa). Available with the end connections listed below:

<b>Model No.</b>	<b>Size in. (mm)</b>	<b>End Connections</b>
FIREKING Fig. No. NF300F	2-1/2, 3, 4, 5, 6, 8, 10, 12 (65, 80, 100, 125, 150, 200, 250 and 300)	Flange × Flange (ANSI, ISO, JIS)
FIREKING Fig. No. NG300F	2-1/2, 3, 4, 5, 6, 8, 10, 12 (65, 80, 100, 125, 150, 200, 250 and 300)	Groove × Groove (ANSI, ISO, JIS)
FIREKING Fig. No. NFG300F	2-1/2, 3, 4, 5, 6, 8, 10, 12 (65, 80, 100, 125, 150, 200, 250 and 300)	Flange × Groove (ANSI, ISO, JIS)

<b>Company Name:</b>	The Viking Corp
<b>Company Address:</b>	210 N Industrial Park Dr, Hastings, Michigan 49058, USA
<b>Company Website:</b>	<a href="http://www.vikinggroupinc.com">http://www.vikinggroupinc.com</a>

<b>Listing Country:</b>	United States of America
<b>Certification Type:</b>	FM Approved

## Outside Screw and Yoke Gate Valves

Outside screw and yoke gate valves are recommended for service indoors and in pits outdoors. They are not recommended for throttling service. The stem indicates at a glance whether or not the valve is open. Smaller sizes, 3/4 through 2 in. NPS inclusive, are of bronze. Large sizes, 2 1/2 through 14 in. NPS inclusive, are of iron, bronze mounted. One manufacturer makes valves of bronze up through the 3 in. size. Unless otherwise noted in the listing, these valves have 175 psi (1205 kPa) rated working pressure.

### Models OSF300, OSG300

<b>Model No.</b>	<b>Description</b>	<b>Nominal Pipe Size, in.</b>	<b>Max Working Pressure, psi (kPa)</b>	<b>End Connections</b>
OSF300	Resilient Seated Gate Valves	2-1/2, 3, 4, 5, 6, 8, 10, 12 (65, 80, 100, 125, 150, 200, 250 and 300)	300 psi (2068 kPa)	Flange × Flange (ANSI, ISO, JIS)
OSG300	Resilient Seated Gate Valves	2-1/2, 3, 4, 5, 6, 8, 10, 12 (65, 80, 100, 125, 150, 200, 250 and 300)	300 psi (2068 kPa)	Groove × Groove

<b>Company Name:</b>	Rapidrop Global Limited
<b>Company Address:</b>	Rutland Business Park, Newark Rd, Peterborough PE15WA, United Kingdom
<b>Company Website:</b>	<a href="http://www.rapidrop.com">http://www.rapidrop.com</a>
<b>New/Updated Product Listing:</b>	No
<b>Listing Country:</b>	United Kingdom
<b>Certification Type:</b>	FM Approved

## Inside Screw Gate Valves

Inside screw gate valves are used underground with indicator posts attached or as roadway box valves (curb box installation). FM Approved valves are available with a variety of end connections as indicated in the listings.

Valves having Ring-Tite, Fluid-Tite or Tyton-Joint connections should be anchored in place during installation. Unless otherwise noted in the listing, these valves have 175 psi (1205 kPa) rated working pressure.

### Models PIF, PIG

Resilient Seated Gate Valves. 2 through 12 in. NPS. Valves have a rated working pressure of 300 psi (2070 kPa). Available with the following end connections.

<b>Model</b>	<b>Size in. (mm)</b>	<b>End Connection</b>
PIF	2, 2 1/2, 3, 4, 6, 8, 10, 12 (50, 65, 80, 100, 150, 200, 250, 300)	Flange x Flange (ANSI, BS, EN, JIS)
PIG	2, 2 1/2, 3, 4, 6, 8, 10, 12 (50, 65, 80, 100, 150, 200, 250, 300)	Groove x Groove (AWWA C606)

<b>Company Name:</b>	The Viking Corp
<b>Company Address:</b>	210 N Industrial Park Dr, Hastings, Michigan 49058, USA
<b>Company Website:</b>	<a href="http://www.vikingcorp.com">http://www.vikingcorp.com</a>
<b>New/Updated Product Listing:</b>	No
<b>Listing Country:</b>	United States of America
<b>Certification Type:</b>	FM Approved