



## USQT.S309 Extinguishing System Attachments

[Page Bottom](#)

### Extinguishing System Attachments

[See General Information for Extinguishing System Attachments](#)**POTTER ELECTRIC SIGNAL CO L L C**

S309

1609 PARK 370 PL  
HAZELWOOD, MO 63042 USA

**SPRINKLER SYSTEM ALARM INITIATING DEVICES****WET PIPE, PADDLE TYPE**

Model	Size In.	Pipe Schedule	Max System Pressure psig
VSG	2, 2-1/2, 3, 4	Water Mist	450
		Systems Only	
VSR-F, VSR-FE,	2, 2-1/2, 3,	10-40	450
VSR-FE-2, VS-F	3-1/2, 4, 5,	Steel	
	6, 8, 10		
VSR	2, 2-1/2, 3, 3-1/2,	10-40 Steel	450
	4, 5, 6, 8, 10		
VSR-AT	2, 2-1/2, 3, 3-1/2,	10-40 Steel	450
	4, 5, 6, 8		
VSR-EU	2, 2-1/2, 3, 4, 5, 6, 8	10-40 Steel	450
VSR-S, VSR-S (EU)	1, 1-1/4, 1-1/2, 2	10-40 Steel	300
		Listed Plastic	
		K, L, M Copper	
VSR-SF, VS-SP, VS-SPB	1, 1-1/4, 1-1/2, 2	10-40 Steel	250
		Listed Plastic	
		K, L, M Copper	
VSR-CF, VSR-C	2, 2-1/2, 3,	Listed Plastic	175
	2, 2-1/2, 3, 4	K, L, M Copper	
VSR-SFG, VSR-SG, VSR-SFT, VSR-ST	1, 1-1/4, 1-1/2, 2	Listed Plastic	250

Model VS-SP, VS-SPB for outdoor use with Kit No. 1940037. Models VS-F, VSR-F, VSR-CF, VSR-C, VSR-FE, VSR-FE-2 for outdoor use with Kit No. 1940036.

**DRY-PIPE & WET-PIPE, PRESSURE TYPE**

Model	Oper Pressure psig	Max System Pressure psig
*PS-10	0-20	300
*PS-10A	4-8	300
*PS-100	20-225	300
*PS10-1	4-15	300
*PS10-2	4-15	300
*PS10-1 w/TSK	4-15	300
*PS10-2 w/TSK	4-15	300
*PS10-1 w/TSK and Brass Bushing	4-15	300

*PS10-2 w/TSK and Brass Bushing	4-15	300
*PS-100A	20-175	300
*PS100-2	25-175	300
WFS-B	10	250
WFSPDB	100	250
*WFSR-C	10	250
*WFSR-F	4-8	175
QRS	10-65	175

### SUPERVISORY SIGNAL INITIATING DEVICES

#### PRESSURE DEVICES

Model	Oper Pressure psig	Max System Pressure psig
*PS-40	20-225	300
PS15-2	5-30	300
*PS-40A	20-175	300
*PS40-1	10-60	300
*PS40-2	10-60	300
*PS40-1 w/TSK	10-60	300
*PS40-2 w/TSK	10-60	300
*PS40-1 w/TSK and Brass Bushing	10-60	300
*PS40-2 w/TSK and Brass Bushing	10-60	300
HLS-B	40	250
*PS-120	20-225	300
*PS-120A	20-175	300
*PS120-1	25-175	300
*PS120-2	25-175	250
*PS120-1 w/TSK	25-175	300
*PS120-2 w/TSK	25-175	300
*PS120-1 w/TSK and Brass Bushing	25-175	300
*PS120-2 w/TSK and Brass Bushing	25-175	300

#### CONTROL VALVE DEVICES

Gate Valve	Post Indicator Valve
GVS	PIVS-B
OSYS-B	*PIVSU-A1, -A2
*OSYSU-1, -2, -A1, -A2	*PCVS, PCVS-1, -2

PTS-B Plug Type Switch — Special Application

\*PMS Plug Type Switch — Special Application

\*PTS-C Plug Type Switch — Special Application.

BVS-1", -3/4", -1/2" Supervised Trim Valves.

RBVS, RBVS-T — Retro-fit Ball Valve Supervisory Switch.

#### SUPERVISORY WATER TEMPERATURE DEVICES Steel or Wood Tank

\*TTS-S, TTS-W

#### SUPERVISORY AIR TEMPERATURE DEVICES

RTS-C, RTS-O, for indoor use.

#### WATERLEVEL DEVICES

\*WLS-S (Steel Tank), WLS-W (Wood Tank), WCS

\*For indoor or outdoor use.

Last Updated on 2013-06-18

[Questions?](#)[Print this page](#)[Terms of Use](#)[Page Top](#)

© 2013 UL LLC

When the UL Leaf Mark is on the product, or when the word "Environment" is included in the UL Mark, please search the [UL Environment database](#) for additional information regarding this product's certification.

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2013 UL LLC".

## Electrical Signaling

Electrical protective signaling systems are configurations of components used to produce alarm signals indicative of fire, smoke, sprinkler waterflow or other emergency and to produce supervisory signals indicative of conditions needing attention with respect to protection equipment or watch service. System configurations are classified according to where and how the signals are received. The categories are commonly designated as local, municipal, remote station, proprietary, emergency voice/alarm communication, emergency communication, and central station. Auxiliary systems are either local or proprietary systems interconnected with a municipal system.

This category presents the major system component categories and the integrated system configurations. The selection of components to form a hybrid system should be made only by those skilled in system design. Also, the suitability of any system application should be judged on the basis of the hazard(s) being protected.

## Supervisory Signal Initiating Devices

Supervisory signals indicate non-alarm conditions affecting important parts of a protection system or timed watchman tours. Normal/abnormal functions are monitored by these switches and switch-actuated transmitters.

## Sprinkler System Supervision

Examples of sprinkler supervisory functions are control valve position, tank pressure, tank level, tank temperature, air pressure, fire pump power and fire pump operation.

### Models PIVS-B, PCVS-1, -2

Post Indicator Valve Switch, Models PIVS-B, PCVS-1, -2. For monitoring the open position of post indicator and butterfly valves. Contacts are rated for 15 A at 125/250 V ac and 2.5 A at 0-30 V dc. For indoor or outdoor (NEMA 4) use in ambient temperatures of -40° to 140°F (-40° to 60°C).

Company Name:	Potter Electric Signal Company
Company Address:	1609 Park 370 Place, Saint Louis, Missouri 63042, USA
Company Website:	<a href="http://www.pottersignal.com">http://www.pottersignal.com</a>
New/Updated Product Listing:	No
Listing Country:	United States of America
Certification Type:	FM Approved



**EUROPEAN DECLARATION OF  
CONFORMITY**

98

**ISSUE DATE:** January, 1988

**MANUFACTURER:** **POTTER ELECTRIC SIGNAL COMPANY**  
2081 CRAIG ROAD  
ST. LOUIS, MO 63146  
USA

**PRODUCT:** **VALVE TAMPER SWITCHES**

**MODEL/TYPE REFERENCE:** **OSYSU-1, OSYSU-2, PCVS-1, PCVS-2**

**THE UNDERSIGNED HEREBY DECLARES, ON BEHALF OF THE POTTER ELECTRIC SIGNAL CO. OF ST. LOUIS MISSOURI, USA THAT THE ABOVE PRODUCT, TO WHICH THIS DECLARATION RELATES IS IN CONFORMITY WITH THE PROVISIONS OF:**

**DIRECTIVES:** **COUNCIL DIRECTIVE 73/23/EEC(FEB.19,1973)**  
**ON THE HARMONIZATION OF THE LAWS OF**  
**THE MEMBER STATES RELATING TO**  
**ELECTRICAL EQUIPMENT DESIGNED FOR USE**  
**WITHIN CERTAIN VOLTAGE LIMITS, AS**  
**AMENDED BY:**

**COUNCIL DIRECTIVE 93/68/EEC (JULY 22, 1993)**

**STANDARDS:** **EN 60 947-5-1 1991 LOW VOLTAGE SWITCHGEAR**  
**& CONTROL GEAR**

**THE TECHNICAL CONSTRUCTION FILE REQUIRED BY THIS DIRECTIVE IS MAINTAINED AT THE CORPORATE OFFICE OF:**

**POTTER ELECTRIC SIGNAL COMPANY**  
2081 CRAIG ROAD  
ST. LOUIS, MISSOURI USA

**AND**

**DENKO A/S**  
LYSKAER 8, POSTBOKS 614  
2730 HERLEV, DENMARK

**JACK H. TURNER**  
**V.P. SUPPORT SYSTEMS**