



## EASE-ON

### High Performance Pipe Joint Lubricant

---

#### Description:

EASE-ON is a new water dispersible, high performance pipe joint lubricant which has been certified by NSF for use in potable water supply systems. Its creamy consistency allows the installer to apply a smooth, consistent coating of EASE-ON to both the gasket and the pipe. Combine this with EASE-ON's excellent lubricity and the result is easier, faster and more reliable pipe assembly operations.

The versatility of this formula is exceptional. EASE-ON has a very broad usable temperature range; -10°F to 150°F. And since It also applies equally well to wet or dry surfaces, EASE-ON High Performance Pipe Joint Lubricant can be used in all conditions, all year long, on any type of pipe.

#### Features:

- Certified to NSF/ANSI Std 61-G
- Smooth, Non-Separating Formula
- All-Season, All-Weather Lube
- Water Dispersible
- Biodegradable
- Utilizes Renewable Resources
- FBC System Compatible
- Minimizes Insertion Forces
- Does Not Support Bacteria
- Contains No Petroleum
- Contains No Phosphates
- Non-Toxic
- Certified Low Lead Level (<0.25%)
- Ultra Low VOC Content (< 1.0 g/l)

#### Product Data:

Form: Soft, Viscous Paste

Color: Off White

Odor: Bland

Boiling Point: > 180°F

Flash Point: > 220°F

Water Miscibility: Very Good

Petroleum Content: None

Phosphate Content: None

Pounds per Gallon; approx. 9.3

pH (5% solution); approx. 9.0

# Material Safety Data Sheet

Ease On Water Dispersible Pipe Joint Lubricant

Date of Preparation: September 2011

## Section 1 - Chemical Product and Company Identification

**Product/Chemical Name:** Ease On Water Dispersible Pipe Joint Lubricant

**Chemical Formula:** 11-4

**Manufacturer:** JTM Products, Inc., 31025 Carter Street, Solon, OH 44139, Phone (440) 287-2302, FAX (440) 287-3095  
(CHEM-TEL 24-hour emergency: (800) 255-3924)

## Section 2 - Composition / Information on Ingredients

Proprietary blend of non-hazardous ingredients

## Section 3 - Hazards Identification

☆☆☆☆☆ **Emergency Overview** ☆☆☆☆☆

### Potential Health Effects

**Primary Entry Routes:** Not Hazardous

**Carcinogenicity:** IARC, NTP, and OSHA do not list the ingredients in Ease On Water Dispersible Pipe Joint Lubricant as carcinogens.

**HMIS**

**H** 1

**F** 0

**R** 0

**PPE**<sup>†</sup>

<sup>†</sup>Sec. 8

## Section 4 - First Aid Measures

**Eye Contact:** Flush with copious volumes of water for 15 minutes while holding eyelids open.

**Skin Contact:** Wash with water.

*If irritation persists, call a physician.*

## Section 5 - Fire-Fighting Measures

**Flash Point:** >220 °F (>104 °C)

**Flash Point Method:** NA, contains water

**Autoignition Temperature:** NA

**Extinguishing Media:** Water, water fog, alcohol foam, carbon dioxide or dry chemical are all suitable.

**Unusual Fire or Explosion Hazards:** None

**Hazardous Combustion Products:** None

**Fire-Fighting Instructions:** Do not release runoff from fire control methods to sewers or waterways.


**Fire-Fighting Equipment:** Because fire may produce toxic thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full facepiece operated in pressure-demand or positive-pressure mode.

**LEL:** NA

**UEL:** NA

**Flammability Classification:** 0

**NFPA**



## Section 6 - Accidental Release Measures

**Spill /Leak Procedures:** This product is a biodegradable soap.

**Containment:** For large spills, dike far ahead of spill for later disposal.

**Cleanup:** Place the bulk of any spilled material into drums, then rinse any remaining material to sewage treatment facility, in accordance with any applicable regulations.

**Regulatory Requirements:** Follow applicable OSHA regulations (29 CFR 1910.120).

## Section 7 - Handling and Storage

**Handling Precautions:** No special precautions are required.

**Storage Requirements:** No special precautions are required.

**Regulatory Requirements:** No known regulatory requirement for handling and storage.

## Section 8 - Exposure Controls / Personal Protection

**Engineering Controls:**

**Ventilation:** Provide general or local exhaust ventilation systems.

**Administrative Controls:**

**Respiratory Protection:** If respirators are used, OSHA requires a written respiratory protection program that includes at least: medical certification, training, fit-testing, periodic environmental monitoring, maintenance, inspection, cleaning, and convenient, sanitary storage areas.

## Ease On Water Dispersible Pipe Joint Lubricant

**Protective Clothing/Equipment:** Wear chemically protective gloves to prevent prolonged or repeated skin contact. Wear protective eyeglasses or chemical safety goggles, per OSHA eye- and face-protection regulations (29 CFR 1910.133). Contact lenses are not eye protective devices. Appropriate eye protection must be worn instead of, or in conjunction with contact lenses.

**Safety Stations:** Make emergency eyewash stations, safety/quick-drench showers, and washing facilities available in work area.

**Contaminated Equipment:** Launder before reuse. Remove this material from your shoes and clean personal protective equipment.

**Comments:** Never eat, drink, or smoke in work areas. Practice good personal hygiene after using this material, especially before eating, drinking, smoking, using the toilet, or applying cosmetics.

### Section 9 - Physical and Chemical Properties

<b>Physical State:</b> Paste	<b>pH: (@5% solution) =</b> 8.95, >9.5(neet)
<b>Appearance and Odor:</b> off-white paste, bland odor	<b>Water Solubility:</b> completely water dispersible
<b>Odor Threshold:</b> NA	<b>Boiling Point:</b> >220 °F
<b>Vapor Pressure:</b> NA	<b>Freezing/Melting Point:</b> <32 °F
<b>Vapor Density (Air=1):</b> NA	<b>Viscosity:</b> viscous paste
<b>Formula Weight:</b> NA (blend)	<b>Refractive Index:</b> unknown
<b>Density:</b> 9.35 lbs./gal.	<b>% Volatile:</b> ~33
<b>Specific Gravity (H<sub>2</sub>O=1, at 4 °C):</b> 1.121	<b>Evaporation Rate:</b> NA

### Section 10 - Stability and Reactivity

**Stability:** Ease On Water Dispersible Pipe Joint Lubricant is stable at room temperature in closed containers under normal storage and handling conditions.

**Polymerization:** Hazardous polymerization will not occur.

**Chemical Incompatibilities:**

**Conditions to Avoid:** Avoid contact with strong oxidizing agents.

**Hazardous Decomposition Products:** Thermal oxidative decomposition of 27-XL Water Dispersible Pipe Joint Lubricant can produce oxides of carbon and nitrogen.

### Section 11- Toxicological Information

#### Toxicity Data:

**Eye Effects:** Eye irritant [based on blended ingredients].

**Skin Effects:** Slight skin irritant if allowed to remain in contact.

### Section 12 - Ecological Information

**Ecotoxicity: Environmental Fate**

**Environmental Transport:** Unknown. **Environmental Degradation:** Soaps are well known to be biodegradable.

**Soil Absorption/Mobility:** Unknown.

### Section 13 - Disposal Considerations

**Disposal:** Contact your supplier or a licensed contractor for detailed recommendations. Follow applicable Federal, state, and local regulations.

### Section 14 - Transport Information

Not hazardous under DOT regulations.

### Section 15 - Regulatory Information

**EPA Regulations:** OSHA... None; TSCA ... All ingredients appear on inventory;  
CERCLA Section 102 (reportable quantity RQ) 40CFR 302; SARA: not applicable;  
CLEAN WATER ACT .... Contains Sodium Hydroxide, section 311 material  
INTERNATIONAL REGULATIONS... None  
CANADIAN ENVIRONMENTAL PROTECTION ACT (CEPA) ..... none

### Section 16 - Other Information

**Prepared By:** D. Barrer

**Disclaimer:** JTM PRODUCTS, INC. makes no warranty, expressed or implied, as to the accuracy, completeness, or reliability of information contained herein, except that such information is, to the best of JTM's knowledge and belief, accurate as of the date indicated. It is for the purchaser and/or user to decide whether this information is suitable for his purposes.